

SAFETY DATA SHEET

JAMES HARDIE FIBRE CEMENT PRODUCTS

Infosafe No.: GEN35

Version No.: 1.0

ISSUED Date : 9/23/2020

ISSUED by: James Hardie Philippines Inc

1. IDENTIFICATION

GHS Product Identifier

JAMES HARDIE FIBRE CEMENT PRODUCTS

Company Name

James Hardie Philippines Inc

Address

Brgy. San Isidro Cabuyao
Laguna 4025 PHILIPPINES

Telephone/Fax Number

Telephone: (632) 859 5427

Emergency phone number

(02) 8524 1078

Recommended use of the chemical and restrictions on use

Fibre cement products are used in internal lining, external cladding, soffits and eaves lining, and internal/external flooring, applications as per the relevant installation guides.

Other Names

Name	Product Code
HARDIEFLEX® SHEET	
HARDIEFLEX® FLOORING	
HARDIEPLANK® WOODGRAIN	
HARDIEFLEX® SENEPA	
HARDIEFLEX® PRO	
RAB™ BOARD	
CTU	
VILLABOARD™ LINING	
VERSILUX™ WALL & CEILING LINING	
HARDIEPANEL® SMOOTH	
HARDIEFLEX® EAVES PLAIN	
HARDIEFLEX® EAVES PERFORATED	
HARDIEFLEX® EAVES SLOTTED	
HARDIEPLANK® CEDARMILL	
HARDIEPLANK® SMOOTH	
HARDIEPATTERN™ PANEL	
HARDIEPANEL® COMPRESSED PANEL	
SCYON™ STRIA™ CLADDING	
HARDIETEX™	
EXOTEC™ FAÇADE PANEL	
SCYON™ AXON™ CLADDING	
PRIMELINE™ HERITAGE	
PRIMELINE™ NEWPORT	
EASYLAP™ PANEL	
PRIMELINE™ CHAMFER	

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Carcinogenicity category 1A

STOT Repeated Exposure: Category 1

Signal Word (s)

DANGER

Hazard Statement (s)

May cause cancer by inhalation. Causes damage to organs (lungs and respiratory system) through prolonged or repeated exposure by inhalation.

Pictogram (s)

Health hazard



Precautionary statement – Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash contaminated skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention.

Precautionary statement – Disposal

Dispose of contents/container to an approved waste disposal plant.

Other Information

IMPORTANT NOTE(S)

The following classification applies to any respirable crystalline silica dust potentially released from James Hardie Fibre Cement products, e.g. during cutting, drilling, grinding or rebating in the course of installation of this product. The intact fibre cement products are not expected to result in any adverse toxic effects.

Other Classifications

The dust and fibres of this substance may be irritating to the skin and respiratory tract as a result of physical (mechanical) reaction (i.e. scratch). The irritation is not a result of a chemical reaction.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition

The exact ratio of components will vary between specific products. Trace quantities of impurities are also likely.

Ingredients

Name	CAS	EINECS	Proportion
Quartz [Silica Crystalline]	14808-60-7	238-878-4	10-<60 %
Calcium Silicate Hydrate	1344-96-3	-	10-50 %
Cellulose	9004-34-6	232-674-9	<15 %
Calcium Silicate	1344-95-2	215-710-8	<10 %
Ingredients determined not to be hazardous			Balance

4. FIRST-AID MEASURES

First Aid Measures

General Information:

If medical advice is needed, have product label at hand. If you feel that you may have been harmed or irritated by this product, you should call (02) 8524 1078 (24 hr, 7 days a week emergency response service). If shortness of breath or other health concerns develop after exposure to dust from the product, seek medical attention.

Inhalation

IF INHALED: Dusts may cause irritation. If experiencing irritation, remove to fresh air. Drink water to clear throat. If shortness of breath or wheezing develops, seek medical attention. Call (02) 8524 1078 (24 hr, 7 days a week emergency response service) or doctor/physician if you feel unwell.

Ingestion

Due to the nature of the product, this route of exposure is not expected under normal conditions. Give a glass of water to drink. If a substantial quantity has been swallowed, call (02) 8524 1078 (24 hr, 7 days a week emergency response service).

Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical advice if irritation occurs or persists.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Apply continuous irrigation with water for at least 15 minutes holding eyelids apart. If eye irritation occurs: Get medical advice.

First Aid Facilities

Ready access to running water is recommended.

Eyewash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, extinguishing powder, foam, fog sprays, water jets.

Hazards from Combustion Products

Non-flammable material.

Specific Hazards Arising From The Chemical

This product is non-flammable.

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. Fight fire from safe location.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

This product is not considered flammable or ecotoxic.

If a significant spill of dust occurs:

Wear protective equipment to prevent skin, eye and respiratory exposure to dusts.

Clear area of any unprotected personnel.

Avoid creating dust. If appropriate, use a gentle water spray to wet dust to minimise further dust generation.

Methods And Materials For Containment And Cleaning Up

Clean-up method: If possible to wet the dust, wet and sweep up the solid. Dry sweeping should not be attempted. Vacuuming with a HEPA vacuum is recommended. Do not wash material down stormwater drains.

Spills & Disposal

Collect recoverable material into labelled containers for recycling or salvage. This material may be suitable for approved landfill.

Dispose of only in accordance with all regulations. See section 13.

Personal Precautions

Wear protective equipment to prevent eye contamination and the inhalation of dusts. Work up wind or increase ventilation.

Other Information

Fibre cement products in their intact state do not present a fire, health or environmental hazard. The mentioned precautions apply to spills and releases of dust generated during cutting, rebating, drilling, routing, sawing or abrading fibre cement.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Keep exposure to crystalline silica dust to a minimum, and minimise the quantities of dust in work areas.

During installation and use of this product: Wherever possible, practices likely to generate dust should be carried out in well-ventilated areas (e.g.outdoors).

Minimise dust creation by using the recommended tooling and cutting methods. (refer to the relevant installation guide and James Hardie Best Practice Guide for tips on the safe handling of these products).

Work area should be cleaned regularly by wet sweeping or vacuuming with a HEPA vacuum.

Keep away from incompatible substances (section 10).

Avoid inhalation of dust, and skin or eye contact. Prevent the build up of dust in the work atmosphere. Maintain high standards of personal hygiene i.e. washing hands prior to eating, drinking, smoking or using toilet facilities.

Avoid exposure. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage, including any incompatibilities

Avoid contact with incompatible substances as listed in Section 10.

Store all James Hardie building products in a dry location. Avoid mechanical damage to the product, such as chipping of the edges and corners of the sheets. The product must be laid flat under cover on a smooth surface clear of the ground to avoid exposure to water or moisture.

Store in a cool, well-ventilated area, out of direct sunlight and moisture. Store away from incompatible materials. Ensure that storage conditions comply with applicable local and national regulations.

Corrosiveness

Non corrosive

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

Substance	Regulations	Exposure Duration	Exposure Limit	Units	Notes
Quartz (respirable)	Philippines OELs List	TWA	-	mg/m3	10 mg/m ³ /%SiO ₂ +2, 250/%SiO ₂ +5 Mppcf
Quartz (total dust)	Philippines OELs List	TWA	-	mg/m3	30 mg/m ³ /%SiO ₂ +3

Biological Limit Values

No biological limits allocated.

Other Exposure Information

No exposure standards have been established for this material. As with all chemicals, exposure should be kept to the lowest possible levels.

Inert or Nuisance particulates:

TWA: 15 Mppcf (respirable fraction)

TWA: 50 Mppcf (total dust)

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Source: Philippines OELs List

Appropriate Engineering Controls

The dust created when cutting, drilling, rebating or grinding fibre cement products using high speed tools is hazardous and should be carried out with a local exhaust ventilation system, drawing solid/dust away from workers' breathing zone. If the engineering controls are not sufficient to maintain concentrations of particulates below the exposure standards, suitable respiratory protection must be worn.

If the workplace situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the Exposure Standard as practicable by applying the hierarchy of control required by the Occupational Safety and Health Standards of the Department of Labor and Employment Philippines.

Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe airborne concentrations of dusts are high, you are advised to modify processes or increase ventilation. Personal protection when handling products that may generate silica dust: 1) Refer to the current James Hardie instruction and best practice guide to reduce or limit the release of dust. 2) Warn others in the area to avoid the dust. 3) When using mechanical saw or high speed cutting tools, work outdoors and use a well maintained HEPA vacuum and filter appropriate for capturing fine respirable dust. 4) Wear a correctly fitted, approved dust mask or respirator.

During clean-ups, use a well maintained HEPA vacuum and filter, appropriate for capturing fine respirable dust or use well-maintained HEPA vacuum and filter appropriate for capturing fine respirable dust or use of wet clean-up methods, never dry sweep.

Respiratory Protection

Always use appropriate and correctly fitted respiratory protection equipment when using high speed tooling on fibre cement products. Ideally, select respirators based on the level of exposure to respirable crystalline silica as measured by exposure monitoring. Where high levels of dust are encountered but actual concentrations are unknown, use respirators that offer protection to the highest concentration of respirable crystalline silica, for example a positive pressure respirator with at least a P3 dust filter.

Respiratory Protection devices should conform with the American National Standards Practices for Respiratory Protection (ANSI z88).

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection devices should conform with the American National Standards for Occupational Eye and Face Protection Equipment

(ANSI z87.1).

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Footwear

Wear safety footwear, i.e. steel capped boots. Final choice will vary according to individual circumstances.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended.

Chemical resistant apron is recommended where high quantities of product are cut and/or dust produced.

Other Information

Specific handling instructions:

Cutting outdoors: position cutting station so that wind will blow dust away from the user or others in working area and allow for ample dust dissipation.

Use one of the following methods based on the required cutting rate and job-site conditions:

BEST – Score and snap using carbide-tipped scoring knife or utility knife.

- Fibre-cement shears (electric or pneumatic).

BETTER – Dust reducing circular saw equipped with Hardiblade™ saw blade and HEPA vacuum. Always wear approved dust mask or respirator and warn others in the immediate areas.

GOOD (for low to moderate cutting only) – Dust reducing circular saw with Hardieblade saw blade.

Important Notes:

For maximum protection (lowest respirable dust production), James Hardie recommends always using “Best” level cutting methods where feasible.

NEVER use a power saw indoors.

NEVER use a circular saw blade that does not carry the Hardieblade™ saw trademark, or is of equal or better performance at reducing risk of dust exposure.

NEVER dry sweep – use wet suppression methods or HEPA class vacuum.

NEVER use a grinder or continuous rim diamond blade for cutting.

ALWAYS follow tool manufacturer’s safety recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Solid

Appearance

Grey, solid sheets or planks with various dimensions according to the product profiles

Colour

Grey

Odour

No odour

Decomposition Temperature

Not available

Melting Point

Not available

Boiling Point

Not available

Solubility in Water

Not available

Specific Gravity

Not available

pH

Not available

Vapour Pressure

Not applicable

Vapour Density (Air=1)

Not available

Evaporation Rate

Not available

Corrosiveness

Non corrosive

Odour Threshold

Not available

Viscosity

Not available

Volatile Component

Not applicable

Partition Coefficient: n-octanol/water

Not available

Flash Point

Not flammable

Auto-Ignition Temperature

Not available

Explosion Limit - Upper

Not applicable

Explosion Limit - Lower

Not applicable

Explosion Properties

Not available

Oxidising Properties

Not available

10. STABILITY AND REACTIVITY

Reactivity

Refer to Section 10: Possibility of hazardous reactions

Chemical Stability

Product is non reactive and stable under normal conditions of storage and handling.

Conditions to Avoid

Avoid the creation of dust during processing, handling and installation.

Incompatible materials

Strong oxidising agents, strong acids and ammonia salts.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes.

Possibility of hazardous reactions

Reacts with incompatible materials.

Hazardous Polymerization

Not available

11. TOXICOLOGICAL INFORMATION

Toxicology Information

Summary:

Fibre cement is non-toxic in its intact form. The following applies to respirable dust that may be generated during cutting, rebating, drilling, routing, sawing, crushing or otherwise abrading fibre cement.

Acute Toxicity - Oral

The estimated LD50 (oral, rat) for the mixture is >5,000 mg/kg. Calcium Silicate: 3400 mg/kg (rat).

Acute Toxicity - Inhalation

The substance is not considered acutely toxic if inhaled, however there may be irritation of the respiratory tract if dust is inhaled.

Acute Toxicity - Dermal

No evidence of dermal toxicity.

Ingestion

No adverse effects expected, however ingesting large amounts of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of dusts may irritate the respiratory system.

Chronic exposure to this material may aggravate existing respiratory disorders and lung disorders such as bronchitis, emphysema and asthma. Onset and progression are related to dust concentrations and duration of exposure.

Repeated exposure to respirable crystalline silica dust may lead to silicosis, or other serious delayed lung injury. The onset of silicosis is usually slow and lung damage may occur even when no symptoms or signs of ill-health have occurred. Silicosis can develop to a more serious degree even after exposure has ceased, and may also lead to other diseases including heart disease and scleroderma. Exposure by inhalation may aggravate pre-existing upper respiratory and lung disorders such as bronchitis, emphysema and asthma.

Dusts may cause upper respiratory tract irritation, resulting in coughing and sneezing. Certain susceptible individuals may experience wheezing (spasms of the bronchial airways) upon inhaling dust during cutting, rebating, drilling, routing, sawing, crushing or otherwise abrading fibre cement, and when cleaning up, disposing of or moving the dust.

Skin

This product is not absorbed through the skin. Dust may dry out the skin. The mixture is not considered to be a skin irritant. May cause abrasive irritation in contact with the skin, which can result in redness, itching and possible dermatitis.

Eye

Eye contact may cause mechanical irritation. May result in mild abrasion.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

No ingredient present at concentrations >0.1% is considered a mutagen.

Carcinogenicity

May cause cancer by inhalation. Respirable crystalline silica is classified by International Agency for Research on Cancer (IARC) as carcinogenic to humans by inhalation (Group 1).

The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate. Carcinogenicity of silica appears linked to development of silicosis (see systemic below) followed by complications and, eventually lung cancer.

Reproductive Toxicity

Not considered to be toxic to reproduction.

No ingredient present at concentrations >0.1% is considered a reproductive or developmental toxicant or have any effects on or via lactation.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Causes damage to organs (lungs and respiratory system) through prolonged or repeated exposure by inhalation.

Aspiration Hazard

Not expected to be an aspiration hazard.

Other Information

Systemic:

There may be some irritation of the respiratory tract. This product contains crystalline silica which if it is in the form of a fine respirable dust may cause silicosis in an occupational setting. Exposure to respirable crystalline silica may also affect the immune system and the kidneys.

Aggravation of existing conditions:

Medical conditions which may be aggravated: pre-existing upper respiratory and lung disease such as, but not limited to bronchitis, emphysema and asthma.

Some studies suggest that cigarette smoking increases the risk of silicosis, bronchitis and lung cancer in persons also exposed to crystalline silica.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Summary:

These products are not considered ecotoxic.

Supporting Data:

Aquatic: These products are not considered to be toxic in the aqueous environment.

Soil: These products are not considered to be toxic in the soil environment.

Biocidal: Not designed as a biocide.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Restrictions: There are no product-specific restrictions. However, state and local disposal regulations may apply. Note that state and local disposal regulations may differ from federal disposal regulations.

Product Disposal

Disposal of this product must comply with the requirements of state and local disposal regulations. If there are no applicable regulations, dispose of in a secure landfill, or in a way that will not expose others to dust.

Container Disposal

Contaminated packaging: not applicable.

14. TRANSPORT INFORMATION

Transport Information

Not classified as Dangerous Goods for transport by road and rail.

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

U.N. Number

None Allocated

UN proper shipping name

Not dangerous for conveyance under UN code

Transport hazard class(es)

None Allocated

Packing Group

None Allocated

UN Number (Air Transport, ICAO)

None Allocated

IATA/ICAO Proper Shipping Name

Not dangerous for conveyance under IATA code

IATA/ICAO Hazard Class

None Allocated

IATA/ICAO Packing Group

None Allocated

IMDG UN No

None Allocated

IMDG Proper Shipping Name

Not dangerous for conveyance under IMO/IMDG code

IMDG Hazard Class

None Allocated

IMDG Pack. Group

None Allocated

IMDG Marine pollutant

No

Transport in Bulk

Not available

Special Precautions for User

Not available

15. REGULATORY INFORMATION

Regulatory information

This product contains ingredient(s) from the High Volume Chemical List of EMB Memorandum Circular No.010-2017.

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Created: September 2020

References

JOINT DTI-DENR-DA-DOF-DOH-DILG-DOLE-DOTC ADMINISTRATIVE ORDER NO. 01 Series of 2009.

Occupational Safety & Health Standards as Amended-RULE 1070.

Republic Act No. 6969 Act to control toxic substances and hazardous and nuclear wastes, providing penalties for violations thereof, and for other purposes.

Department Order No. 136-14 Guidelines for the Implementation of Globally Harmonized System (GHS) in Chemical Safety Program in the Workplace.

DENR Administrative Order No. 2015-09 Rules and Procedures for the Implementation of the Globally Harmonized System (GHS) of Classification and Labelling of Chemicals in Preparation of Safety Data Sheet (SDS) and Labeling Requirements of Toxic Chemical Substances.

EMB Memorandum Circular No.2015-011 Guidance manual for DAO 2015-09.

EMB Memorandum Circular No.2015-01 Guidelines in the Implementation of Globally Harmonized System (GHS) Classification and Labeling Requirements for High Volume Chemicals (HVCs).

Implementing rules and regulations on controlled chemicals pursuant to Section 4-C to 4-F of PD No. 1866 as amended by RA No. 9516.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.
The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.
Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.